

New Energy - Shielded Cable Waterproof Connector HSM - EMC

Spring Shielded Cable Waterproof Connector



Spring Shielded Cable Waterproof Connector HSM-EV-TH								
Thread Specification	Wire Harness Parameters				Joint Installation Parameters			
	Cable			Wire Nose	Thread Length	Installation Height	Joint Opposite Side	Nut Opposite Side
	mm ²	Shielding Layer Dg3-Dg2	Outer Diameter	W	C	H	SW1	SW2
M20x1.5	35	7 ~ 11	8 ~ 11	11	8	32	24	24
M20x1.5	35	7 ~ 11	11 ~ 14.3	14.3	8	32	24	24
M20x1.5	35	7 ~ 11	9 ~ 12	12	8	32	24	24
M25x1.5	50	11 ~ 17	12 ~ 17	17	8	35	30	30
M25x1.5	50	12.5 ~ 19.5	16 ~ 19.5	19.5	8	35	30	30
M25x1.5	25	15.5 ~ 20.5	17 ~ 20.5	20.5	8	32	30	30
M32x1.5	70	15.5 ~ 26.5	19 ~ 26.5	26.5	10	35	34	34
M32x1.5	70	15.5 ~ 22	19 ~ 22	22	10	34	34	34
M32x1.5	50	11-17	12-17	17	8	32	34	30
M32x1.5	25	15.5 ~ 20.5	17 ~ 20.5	20.5	8	32	34	30
M32x1.5	50	12.5 ~ 19	14 ~ 19	19	8	35	34	30